

Data Sheet

Chevron

Solid



HØRNING Chevron is a French herringbone floor with distinct lines in a classic and sophisticated expression.

HØRNING Chevron is available in a variety of dimensions with tongue and groove on all 4 sides, sharp edges and untreated as standard. Oiled or lacquered surface is available upon request.

Environmental certifications are provided upon request.

Feel free to contact us if you desire custom processing, alternative wood species, dimensions, or have questions regarding delivery times, for example.

Chevron – Data Sheet

HØRNING Chevron combines historical floor design with modern trends in contemporary architecture.

Dimensions:

Thickness: 16 / 20 mm

Width: 70 / 100 / 120 / 150 mm

Length: 410 / 440 / 600 / 800 / 1000 mm

Other dimensions available upon request.

For installation on a solid subfloor.

Wood species:

Oak

Other wood species are available upon request.

Production tolerances:

Thickness: +/- 0,2 mm

Width: +/- 0,2 mm

Perpendicular: Up to 0,2 mm

Moisture content in the wood:

8% +/- 2%

Profile:

Delivered with tongue and groove and sharp edges or micro bevel on 4 sides.

Surface:

Delivered as standard untreated. Can be supplied with pre-finished surface treatment with oil or lacquer.

Grades:

Grades vary from wood specie and dimension. Wood is a natural material, thus there will always be variations compared to descriptions and photos. Samples will only show dimension and construction and not the grade. It is certain that variations will exist between small samples and the actual deliveries.

Exquisite

General uniform colour and wood structure. Variations due to growth conditions will exist. In principle free of knots and sapwood. Whirls, small scratches, cross grains and brown heart may be found to a small extent.

Living

A more characteristic look with natural colours and wood structure. In principle free of open knots, cracks, pith etc. Whirls, healthy knots, small scratches, cross grains and silicon stains may be found. Sapwood or brownheart will be found depending of the wood specie.

Country

A very characteristic look with all-natural colour variations and structures. Knots, sapwood and brownheart is found. Very small open knots and scratches may be found.

Under-floor heating:

Under-floor heating may be used. Please see the installation guide.

Indoor climate:

It is important that the surface temperature never exceeds 27 degrees!

The relative humidity in the air (R.H.) must always be between 35-65% before, during and after installation.

Always study the installation guide from HØRNING prior to installation.

Fire classification:

Dfl-s1

Request a declaration of performance (DOP).

Environment:

FSC and/or PEFC on request.

HØRNING is Eurofins Indoor Air Comfort Gold certified, and has a wide range of certified products.

EPD (Environmental Product Declaration) is available on selected products.

CE-certification:

HØRNING floors are generally CE certified in accordance with the EC declaration regarding wooden floors for indoor usage EN 14342.