



# End Grain Mosaic

## *Data Sheet*

**HØRNING End Grain Mosaic** consists of small, square blocks that are cut against the grain.

This results in an extremely durable floor, particularly recommended for high traffic areas.

Upon delivery, the end grain mosaic has already been laid in cube patterns, glued onto a mesh. This makes for simple, effective fitting.

### **Highlighted Features:**

- A *Wholehearted* pledge to use the remains of the log, reducing waste in the production
- A simplified installation compared to traditional end grain flooring
- Documented sustainability credentials towards certifications such as BREEAM, DGNB, and LEED through EPDs and Eurofins

If you have any questions or need advice, please don't hesitate to contact us.

### **Hørning Parket A/S**

Christiansmindevej 12  
DK-8660 Skanderborg

T: +45 7027 6600  
W: [horningfloor.com](http://horningfloor.com)  
E: [sales@horningfloor.dk](mailto:sales@horningfloor.dk)



[epddanmark](http://epddanmark.com)

# End Grain Mosaic

## Data Sheet

**HØRNING End Grain Mosaic** is made of small solid square blocks, which are cut opposite the grain and delivered on net.

### Dimensions & Construction

Types of Wood:	Oak, Smoked Oak
Thickness:	18 mm
Width:	23 mm
Length:	69 mm / 140 x 558 mm on net
Patterns:	Square pattern on net

### Description of Gradings

#### Object:

A vibrant, natural interplay of colours with consistent variations. Chips and small, healthy knots are acceptable. In principle, it is free from surface scratches and ingrown bark. Gradings vary, depending on type of wood.

Wood is a wonderful natural material, so variation vis-à-vis descriptions and photos will always occur. Any samples show only dimension and texture and cannot show the grading. Variations will certainly occur between small samples and actual deliveries for large areas.

### Profile

Sharp edged, without tongues/ grooves.

### Tolerances

Our 100 years of production experience allows us in several product types to offer even lower tolerances according to DIN 68702.

Thickness:	+/- 0.5 mm
Width:	+/- 0.5 mm
Length:	+/- 1.0 mm

### Surface

Untreated.

### Installation Method

Fully Gluing	x
Screwing and Nailing	
Floating	

### Underfloor Heating

Underfloor heating may be used – please see our installation guide.

### Indoor Climate

It is important that the surface temperature never exceeds 27 degrees!

The relative humidity in the air (R.H.) must always be between 35-65% before, during, and after installation.

**Always study the installation guide from Hørning prior to installation.**

### Fire Resistance Class

Dfl-s1 (Untreated)  
Declaration of Performance (DOP) upon request.

### CE Certification

The product is CE marked in accordance with the European standard regarding wooden floors for indoor usage EN 14342.



Oak



Smoked Oak

### Hørning Parket A/S

Christiansmindevej 12  
DK-8660 Skanderborg  
T: +45 7027 6600  
W: [horningfloor.com](http://horningfloor.com)  
E: [sales@horningfloor.dk](mailto:sales@horningfloor.dk)

### Environment



**To find further information and inspiration, please visit our website.**

FSC® and/or PEFC available upon request.  
Eurofins Indoor Air Comfort Gold certified.  
EPD available upon request for selected products.