



# Mastic E850 Filler

## Data Sheet

**HØRNING Mastic E850 Filler** is used for indoor and outdoor repairs without finishing, as well as full filling of floors.

### Highlighted Features:

- During the drying process, the filler does not sink or crack
- Short drying time
- Water-based and ready for use
- Minimal dust when grinding

If you have any questions or need advice, please don't hesitate to contact us.

### Hørrning Parket A/S

Christiansmindevej 12  
DK-8660 Skanderborg

T: +45 7027 6600  
W: [horningfloor.com](http://horningfloor.com)  
E: [sales@horningfloor.dk](mailto:sales@horningfloor.dk)



# Mastic E850 Filler

## *Data Sheet*

### Product

Water-based filler – ready for use.  
Made from various dry matter (>80%), water app. 20%.

### Technical Data

Colour:	4 standard colours
pH Value:	7 - 8
Density:	About 1.68 kg/l
Working Temperature:	Between 5°C and 30°C

### Condition of Use

HØRNING Mastic E850 Filler can be used for both indoor and outdoor repairs without finishing.

The filler is ready to use for full filling of unfinished wood floors, e.g. industrial parquet.

It is important to store the filler in a closed bucket.

After using the tools, clean them with water.

### Note

Protective clothing or venting is not required for HØRNING Mastic E850 Filler.

During drying time, HØRNING Mastic E850 Filler does not sink or crack. Additionally, the filler has a short drying time.

The filler is very resistant to moisture, and minimal dust occurs when grinding.

### Packaging

7 kg plastic bucket.

### Storage

Store HØRNING Mastic E850 Filler cold but frost-free.

The filler can be stored up to 1 year. The recommended room temperature is between 5°C and 30°C.



Ash

Oak

Wenge

Black

### Hørrning Parket A/S

Christiansmindevej 12  
DK-8660 Skanderborg  
T: +45 7027 6600  
W: [horningfloor.com](http://horningfloor.com)  
E: [sales@horningfloor.dk](mailto:sales@horningfloor.dk)

### Environment

