



Origin Plank

Data Sheet

HØRNING Origin Plank is made from carefully selected wood.

This unique solid floor is available in special dimensions in thicknesses up to 35 mm, width up to 40 cm and lengths up to 16 m.

Highlighted Features:

- A unique flooring solution that will make the room appear bigger and longer
- An exceptionally durable solid wooden floor, crafted to last for generations
- The option to install on joists
- Documented sustainability credentials towards certifications such as BREEAM, DGNB, and LEED through EPDs and Eurofins

If you have any questions or need advice, please don't hesitate to contact us.

Hørning Parket A/S

Christiansmindevej 12
DK-8660 Skanderborg

T: +45 7027 6600
W: horningfloor.com
E: sales@horningfloor.dk



[epddanmark](http://epddanmark.com)

Origin Plank

Data Sheet

Dimensions & Construction

Type of Wood:	Oak		
Thickness:	22 mm	30 mm	
Width:	210/250/300/350 mm	210/250/300/350 mm	
Length:	3300-6000 mm		
Type of Wood:	Douglas		
Thickness:	25 mm	30 mm	35 mm
Width:	200/250/300 mm	200/250/320/400 mm	250/320/400/500 mm
Length:	3000-6000 mm	3000-6000 mm	3000-6000 mm
Gradings:	Exquisit/Living, Living, Country		
Moisture Content:	8% +/- 2%		

The planks are untreated upon delivery. You ought to sand then slightly and surface treat them after installation in order to achieve the perfect result, which characterises genuine solid wooden floors.

Description of Lengths

HØRNING Origin Plank is delivered both in dropping lengths, in the strongest dimensions, and also in fixed room lengths.

When selecting fixed room lengths, the rooms must be measured. Be sure that if crooked spaces are measured in several places, so no boards are provided that are too short! The shelves are delivered in fixed lengths for every 50 cm, as long as the stock of raw wood reaches.

Be aware that boards throughout room lengths must be able to be handled from the truck through a window or door, and through possibly other rooms, and they must be handled in the room where they are to be fitted!

Remember to include any waste. This will depend on the length of the planks and the width of the rooms as measured against the width of the planks.

Description of Gradings

Grades vary from types of wood and dimension.

Hørning's many different plank floors are made of fresh wood modified to the dimensions of the plank floors. In general wide/long dimensions will show most variations, knots, fillings, etc.

Wood is a natural material, and variations compared to descriptions and photos will always exist. Samples will only show dimensions and construction and cannot show the grade. It is certain that variations will be found between small samples and the actual deliveries.

Exquisit:

General uniform colour and wood structure. Variations, due to growth conditions, will always exist. Healthy knots and a few fillings of knots and minor cracks may be found. Whirls, small scratches and cross grains, sapwood, and brownheart may be found to a small extent. Also this grade involves, that the wider and longer the planks are, the more and bigger variations, knots, etc. will be found.

Living:

A more characteristic look with natural colours and wood structure. In principle free of open knots, cracks, pith, etc. Whirls, healthy knots, small scratches, cross grains, and silicon stains will be found depending of the wood species. Knots occur naturally in both small and big dimensions. Open knots, cracks, etc. are filled. Sapwood, brownheart, and pith will be found depending of the wood species.

Country:

Very characteristic look with natural colour variations and wood structures. Knots of all types, sapwood, brownheart, filled knots, and cracks will be found. Open knots, cracks, and fillings may be found.

Origin Plank

Data Sheet

Ordering & Delivery Time

HØRNING Origin Plank flooring is unique in every sense of the word and places heavy demands on the manufacturing process. Any and all orders are manufactured for the individual clients according to their specifications.

It may take up to two years from the time of cutting down the trees until the planks are ready for installation. Part of the process is about ensuring supplies of planks in the correct lengths and widths, which in itself is a difficult task. This means that once an order has been received by the sawmill, the raw planks are cut in accordance with the specifics of this particular order and consequently, you cannot change your mind at this point. You cannot cancel the order and the quantities cannot be reduced!

Then the planks are dried to achieve the correct moisture content before the floor is manufactured. The drying process for large dimensions is complex and therefore the time of delivery may vary slightly from what was initially anticipated. Any delivery times may thus always be subject to change!

Delivery & Reception

HØRNING Origin Plank requires careful logistics coordination, from shipment to delivery, receipt, storage and storage.

The planks are due to the long lengths delivered by crane car and will be unloaded from the side of the truck. There must be somebody else present when the planks are delivered and they must be ready to carry in the planks immediately. The planks must be hand carried 1 at a time! The planks must be installed 1-2 days after having been placed in the location where they are planned to be.

If the planks are kept at an air humidity of, for example, over 50% R.H. , they will absorb moisture and thereby expand, which may cause contraction later.

Profile

Tongue/groove on 4 sides and comes with either sharp edges or microbevels.

Tolerances

Our 100 years of production experience allows us in several product types to offer even lower tolerances.

Oak:

Thickness:

Unfinished +/- 1.0 mm

Prefinished +/- 0.3 mm

Width: +/- 1.0 mm

Length: - 0 mm / + 50 mm

Perpendicular: ≤ 0.2%

Douglas:

Thickness:

Unfinished +/- 1.0 mm

Prefinished +/- 0.3 mm

Width: +/- 1.0 mm

Length: - 0 mm / + 50 mm

Perpendicular: ≤ 0.2%

CE Certification

The product is CE marked in accordance with the European standard regarding wooden floors for indoor usage EN 14342.

Surface

Untreated.

Underfloor Heating

Underfloor heating may be used – please see our installation guide.

Installation Method

Fully Gluing	x
Screwing and Nailing	x
Floating	

Indoor Climate

It is important that the surface temperature never exceeds 27 degrees!

The relative humidity in the air (R.H.) must always be between 35-65% before, during, and after installation.

Always study the installation guide from Høorning prior to installation.

Fire Resistance Class

Dfl-s1 (Untreated)
Cfl-s1 (Surface Treatment)
Declaration of Performance (DOP) upon request.

Høorning Parket A/S

Christiansmindevej 12
DK-8660 Skanderborg

T: +45 7027 6600
W: horningfloor.com
E: sales@horningfloor.dk

To find further information and inspiration, please visit our website.

Environment



FSC® and/or PEFC available upon request.
Eurofins Indoor Air Comfort Gold certified.
EPD available upon request for selected products.