



Solid Line®

Data Sheet

HØRNING Solid Line® is available in a range of wood species and several dimensions.

Solid Line can be delivered pretreated or with oil or lacquer for efficient installation, also increasing resistance to dirt, pressure marks, and wear.

Highlighted Features:

- Short time between start-up and assembly of finished flooring
- There is no risk that assembled elements subsequently “pop up” and require repair, grinding, and new surface treatment
- Ideal for renovating due to the small thickness of the sheets
- Documented sustainability credentials towards certifications such as BREEAM, DGNB, and LEED through EPDs and Eurofins

If you have any questions or need advice, please don't hesitate to contact us.

Hørning Parket A/S

Christiansmindevej 12
DK-8660 Skanderborg

T: +45 7027 6600
W: horningfloor.com
E: sales@horningfloor.dk



[epddanmark](http://epddanmark.com)

Solid Line®

Data Sheet

Dimensions & Construction

Types of Wood:	Maple, Ash, Oak, Smoked Oak, Walnut
Thickness:	10/15 mm
Width of Sheet:	163/245 mm
Length of Sheet:	490 mm
Width of Single Strips:	10/16/22 mm

Solid Line is supplied on prefinished sheets of 10x163 / 245x490 mm, made up of small strips held together by wood stability strips on the backside of the sheet.

Other dimensions and types of wood are available on request.

Moisture Content: 8% +/- 2%

Description of Gradings

Object:

A very characteristic look with all natural colour variations and structures. Knots, fillers, sapwood, and brown heart is found.

Grading varies by wood species and dimension. Wood is a natural material, variation in terms of descriptions and photos will always occur. Possibly. Samples show only dimensions and construction and can not display the sorting. Variations will certainly occur between small samples and ctual deliveries of larger areas.

Surface Treatment

Solid Line can be delivered oiled, lacquered, or unfinished.

An oiled floor has increased resistance to dirt and must be treated with care oil before using the floor. The oil gives a silk mat look and emphasises the unique character of an original wooden floor.

Unlike painted surfaces, it is possible to perform repairs on a range of occasions. The surface is hypoallergenic, easy to clean, and easy to maintain.

Treat Solid Line with a maintenance oil for protection after the installation.

Profile

Tongue and groove on all 4 sides. Sharp edges. The boards are profiled after the surface treatment - resulting in a beautiful floor with hardly any visible joints.

Tolerances

Our 100 years of production experience allows us in several product types to offer even lower tolerances.

Thickness:

Unfinished +/- 0.2 mm

Prefinished +/- 0.5 mm

Width: +/- 0.2 mm

Length: +/- 2.0 mm

Installation Method

Fully Gluing	x
Screwing and Nailing	
Floating	

Underfloor Heating

Underfloor heating may be used - please see our installatoin guide.

Indoor Climate

It is important that the surface temperature never exceeds 27 degrees!

The relative humidity (R.H.) must be between 35-65% at approx. 20°C - both before, during, and after assembly.

Always study the installation guide from Hørning prior to installation.

Fire Resistance Class

Dfl-s1 (untreated)
Cfl-s1 (Surface Treatment)
Decalration of Performance (DOP) upon request.

CE Certification

The product is CE marked in accordance with the European standard regarding wooden floors for indoor usage EN 14342.



Ash Object



Oak Object



Smoked Oak Object

Hørning Parket A/S

Christiansmindevej 12
DK-8660 Skanderborg
T: +45 7027 6600
W: horningfloor.com
E: sales@horningfloor.dk

Environment



To find further information and inspiration, please visit our website.

FSC® and/or PEFC available upon request. Eurofins Indoor Air Comfort Gold certified. EPD available upon request for selected products.