



Solid Parquet Block

Danish Made

Endless possibilities and the market's lowest tolerances.

Short blocks, long blocks, and pattern blocks in a variety of wood species.

Highlighted Features:

- A stunning flooring solution, as featured in the iconic Aarhus City Hall designed by Arne Jacobsen
- An exceptionally durable solid wooden floor, crafted to last for generations
- A true legacy of Danish craftsmanship
- Documented sustainability credentials towards certifications such as BREEAM, DGNB, and LEED through EPDs and Eurofins

If you have any questions or need advice, please don't hesitate to contact us.

Hørning Parket A/S

Christiansmindevej 12
DK-8660 Skanderborg

T: +45 7027 6600
W: horningfloor.com
E: sales@horningfloor.dk



Solid Parquet Block

Danish Made

Dimensions & Construction

Short Block

To be installed in staggered pattern on a firm base.

Dimensions: 15/20 mm x 65.5 mm x 300-600 mm

Long Block

To be installed in downward sequence or on a firm base.

Dimensions: 20 mm x 63 mm x 800-1200 mm

Pattern Block

To be installed on a firm base.

Dimensions: 15/20 mm x 65.5 mm x 327.5/393/458.5 mm

Please request any custommade measurements and ranges.

Moisture Content: 8% +/- 2%

Species	Select	Nature	Rustic
Ash	X	X	X
Bilinga		X	
Beech		X	
Doussie		X	
Oak	X	X	X
Jatoba		X	
Merbau		X	
Smoked Oak		X	
Teak		X	
Walnut		X	
Wengé		X	

Description of Gradings

Grades vary from wood species and dimension. Wood is a natural material, thus there will always be variations compared to descriptions and photos. Samples will only show dimension and construction and not the grade. It is certain that variations will exist between small samples and the actual deliveries.

Select:

General uniform colour and wood structure. Variations, due to growth conditions, will exist. In principle free of knots and sapwood. Whirls, small scratches, cross grains, and brown heart may be found to a small extent.

Nature:

A more characteristic look with natural colours and wood structure. In principle free of open knots, cracks, pith, etc. Whirls, healthy knots, small scratches, cross grains, and silicon stains may be found. Sapwood or brownheart will be found depending of the wood species.

Rustic:

A very characteristic look with natural colour variations and structures. Knots, sapwood, and brownheart is found. Very small open knots and scratches may be found.

Profile

Available with tongue/groove and sharp edges. Pattern strips are available as both left and right strips in equal numbers.

Tolerances

Our 100 years of production experience allows us in several product types to offer even lower tolerances.

Thickness: +/- 0.1 mm

Width: +/- 0.1 mm

Length: +/- 0.1 mm

Perpendicular: +/- 0.05 mm

Surface

Untreated.

Installation Method

Fully Gluing	X
Screwing and Nailing	X
Floating	

Underfloor Heating

Underfloor heating may be used – please see our installation guide.

Indoor Climate

It is important that the surface temperature never exceeds 27 degrees!

The relative humidity in the air (R.H.) must always be between 35-65% before, during, and after installation.

Always study the installation guide from Hørning prior to installation.


Fire Resistance Class

Dfl-s1 (Untreated)
Declaration of Performance (DOP) upon request.


CE Certification

The product is CE marked in accordance with the European standard regarding wooden floors for indoor usage EN 14342.


Patterns




Herringbone




English




Ladder




Triple Herringbone




Dutch



Square



Parallel



Staggered

Hørning Parket A/S

Christiansmindevej 12
DK-8660 Skanderborg

T: +45 7027 6600
W: horningfloor.com
E: sales@horningfloor.dk

To find further information and inspiration, please visit our website.

Environment



FSC® and/or PEFC available upon request.
Eurofins Indoor Air Comfort Gold certified.
EPD available upon request for selected products.