



Solid Parquet Block

European Made - Data Sheet

High quality solid parquet block.

Short blocks and pattern blocks in high quality and good gradings. Handled with the same dedication that characterises Hørning.

Special dimensions and wood species can be supplied on request.

Highlighted Features:

- Consistent high quality craftsmanship in every piece
- A wide range of design options to suit any space
- An exceptionally durable solid wooden floor, crafted to last for generations
- Documented sustainability credentials towards certifications such as BREEAM, DGNB, and LEED through EPDs and Eurofins

If you have any questions or need advice, please don't hesitate to contact us.

Hørning Parket A/S

Christiansmindevej 12
DK-8660 Skanderborg

T: +45 7027 6600
W: horningfloor.com
E: sales@horningfloor.dk



[epddanmark](http://epddanmark.com)

Solid Parquet Block

European Made - Data Sheet

Short Blocks

To be installed in staggered pattern on a firm base.

Pattern Blocks

To be installed in a pattern on a firm base.

Dimensions & Construction

Types of Wood:	Oak	Ash
Thickness:	16/22 mm	16/22 mm
Width:	70 mm	70 mm
Length:	350/420/500 mm	350/420/500 mm
Gradings:	Exquisit, Living, Country	
Moisture Content:	8% +/- 2%	

Description of Gradings

Grades vary from wood species and dimension. Wood is a natural material, thus there will always be variations compared to descriptions and photos. Samples will only show dimension and construction and not the grade. It is certain that variations will exist between small samples and the actual deliveries.

Exquisit:

General uniform colour and wood structure. Variations, due to growth conditions, will exist. In principle free of knots and sapwood. Whirls, small scratches, cross grains, and brown heart may be found to a small extent.

Living:

A more characteristic look with natural colours and wood structure. In principle free of open knots, cracks, pith, etc. Whirls, healthy knots, small scratches, cross grains, and silicon stains may be found. Sapwood or brownheart will be found depending of the wood species.

Country:

A very characteristic look with natural colour variations and structures. Knots, sapwood, and brownheart is found. Very small open knots and scratches may be found.

Profile

Available with tongue/groove and sharp edges. Strips for patterns are available as both left and right strips in equal numbers.

Special measurements and productions are available on request.

Tolerances

Our 100 years of production experience allows us in several product types to offer even lower tolerances.

Thickness:

Unfinished +/- 0.2 mm

Prefinished +/- 0.5 mm

Width: +/- 0.2 mm

Length: +/- 0.5 mm

Perpendicular: ≤ 0.2%

Fire Resistance Class

Dfl-s1 (Untreated)
Cfl-s1 (Prefinished)
Declaration of Performance (DOP) upon request.

Surface

Untreated or oiled with clear or coloured oil.

Installation Method

Fully Gluing	x
Screwing and Nailing	x
Floating	

Underfloor Heating

Underfloor heating may be used – please see our installation guide.

Indoor Climate

It is important that the surface temperature never exceeds 27 degrees!

The relative humidity in the air (R.H.) must always be between 35–65% before, during, and after installation.

Always study the installation guide from Hørning prior to installation.

CE Certification

The product is CE marked in accordance with the European standard regarding wooden floors for indoor usage EN 14342.

Hørning Parket A/S

Christiansmindevej 12
DK-8660 Skanderborg

T: +45 7027 6600
W: horningfloor.com
E: sales@horningfloor.dk

To find further information and inspiration, please visit our website.

Environment



FSC® and/or PEFC available upon request.
Eurofins Indoor Air Comfort Gold certified.
EPD available upon request for selected products.