



Solid Plank

Data Sheet

Superb quality in long lanes.

Hørning planks come in different widths and lengths, light and dark woods and in contrasting borders along the walls, etc.

Available in a section of prefinished colours in oil or lacquer, or can be supplied unfinished.

Highlighted Features:

- An extensive range of dimensions to create the desired design expression
- An exceptionally durable solid wooden floor, crafted to last for generations
- The option to install on joists
- Documented sustainability credentials towards certifications such as BREEAM, DGNB, and LEED through EPDs and Eurofins

If you have any questions or need advice, please don't hesitate to contact us.

Hørning Parket A/S

Christiansmindevej 12
DK-8660 Skanderborg

T: +45 7027 6600
W: horningfloor.com
E: sales@horningfloor.dk



epddanmark

Solid Plank

Data Sheet

Dimensions & Construction

European Made

Types of Wood:	Ash, Bilinga, Oak, Jatoba, Merbau, Smoked Oak, Teak, Walnut, Wenge.	
Thickness:	16 mm	20 mm
Width:	100/120/140/150/180 mm	100/120/140/150/180 mm
Length:	800-2600 mm	800-2600 mm
Gradings:	Exquisit, Living & Country	

Danish Made

Types of Wood:	Ash, Merbau	Oak
Thickness:	20 mm	20 mm
Width:	135 mm	135/180 mm
Length:	700-2400 mm	700-2400 mm
Gradings:	Ash comes in grading Select. Oak and Merbau comes in grading Living.	
Other dimensions and types of wood are available on request.		
Moisture Content:	8% +/- 2%	

Description of Gradings

Grades vary from wood species and dimension.

Hørning's many different plank floors are made of fresh wood, modified to the dimensions of the plank floors. In general, wide/long dimensions will show most variations, knots, fillings, etc.

Wood is a natural material, and variations compared to descriptions and photos will always exist. Samples will only show dimensions and construction and cannot show the grade. It is certain that variations will be found between small samples and the actual deliveries.

Select/Exquisit:

General uniform colour and wood structure. Variations, due to growth conditions, will always exist. Healthy knots and a few fillings of knots and minor cracks may be found. Whirls, small scratches and cross grains, sapwood, and brownheart may be found to a small extent. Additionally, this grade involves that the wider and longer the planks are, the more and bigger variations, knots, etc. will be found.

Surface

Delivered filled, sanded, and unfinished as standard. May be delivered with finished surface treatment with oil or mat lacquer upon request.

Installation Method

Fully Gluing	x
Screwing and Nailing	x
Floating	

Tolerances

Our 100 years of production experience allows us in several product types to offer even lower tolerances.

Thickness:

Unfinished	+/- 1.0 mm
Prefinished	+/- 0.3 mm

Width:	+/- 1.0 mm
Length:	+/- 2.0 mm

Perpendicular: ≤ 0.2%

Underfloor Heating

Underfloor heating may be used – please see our installation guide.

Indoor Climate

It is important that the surface temperature never exceeds 27 degrees!

The relative humidity in the air (R.H.) must always be between 35-65% before, during, and after installation.

Always study the installation guide from Hørning prior to installation.

CE Certification

The product is CE marked in accordance with the European standard regarding wooden floors for indoor usage EN 14342.

Fire Resistance Class

Dfl-s1 (Untreated)
Cfl-s1 (Prefinished)
Declaration of Performance (DOP) upon request.

Hørning Parket A/S

Christiansmindevej 12
DK-8660 Skanderborg
T: +45 7027 6600
W: horningfloor.com
E: sales@horningfloor.dk

Environment



epd danmark

FSC® and/or PEFC available upon request.
Eurofins Indoor Air Comfort Gold certified.
EPD available upon request for selected products.