



# Versailles Panel

## *Data Sheet*

**The Versailles pattern consists of beautiful, symmetrical design elements, providing a completely unique expression.**

The patterns can be combined with borders, adding an extra aesthetic dimension.

HØRNING Versailles patterns are available in oak in different gradings.

### **Highlighted Features:**

- A very large range of designs and patterns
- Exclusive solid floor for unique buildings and rooms
- Documented sustainability credentials towards certifications such as BREEAM, DGNB, and LEED through Eurofins

If you have any questions or need advice, please don't hesitate to contact us.

### **Hørrning Parket A/S**

Christiansmindevej 12  
DK-8660 Skanderborg

T: +45 7027 6600  
W: [horningfloor.com](http://horningfloor.com)  
E: [sales@horningfloor.dk](mailto:sales@horningfloor.dk)



# Versailles Panel

## Data Sheet

**HØRNING Versailles Panel** can be crafted in either solid or engineered timber flooring.

### Dimensions & Construction

#### Solid

Type of wood:	Oak
Thickness:	16/21 mm
Width/Length:	790x790 mm/932x932 mm
Gradings:	Exquisit, Living, Country
Additional:	Beveling, brushing and beveling, or hand finished look.

#### Engineered

Type of wood:	Oak
Thickness:	15/20 mm
Width/Length:	800x800 mm/980x980 mm/1500x1500 mm
Wear Layer:	3.8/5.5 mm
Gradings:	Exquisit, Living
Additional:	Bevels Square edges inside the panel, micro bevels on outer edges.

Other types of wood are available on request.

Moisture Content: 8% +/- 2%

### Description of Gradings

Grades vary from wood species and dimension. Wood is a natural material, thus there will always be variations compared to descriptions and photos. Samples will only show dimension and construction and not the grade. It is certain that variations will exist between small samples and the actual deliveries.

#### Exquisit:

General uniform colour and wood structure. Variations, due to growth conditions, will exist. In principle free of knots and sapwood. Whirls, small scratches, cross grains, and brown heart may be found to a small extent.

#### Living:

A more characteristic look with natural colours and wood structure. In principle free of open knots, cracks, pith, etc. Whirls, healthy knots, small scratches, cross grains, and silicon stains may be found. Sapwood or brownheart will be found depending of the wood species.

#### Country:

A very characteristic look with natural colour variations and structures. Knots, sapwood, and brownheart is found. Very small open knots and scratches may be found.

#### Profile

Untreated panels can be delivered with sharp-edges or microbevel on four sides. Treated panels always have microbevel on four sides.

#### Surface

Delivered as standard untreated, filled, and sanded. Inquire about lacquering, oiling, hardwax oiling, brushing, or smoking.

#### Installation Method

Fully Gluing	x
Screwing and Nailing	x
Floating	

#### Underfloor Heating

Underfloor heating may be used – please see our installation guide.

#### Indoor Climate

It is important that the surface temperature never exceeds 27 degrees!

The relative humidity in the air (R.H.) must always be between 35-65% before, during, and after installation.

**Always study the installation guide from Hørring prior to installation.**

#### Fire Resistance Class

Dfl-s1 (Untreated)  
Cfl-s1 (Surface Treatment)  
Declaration of Performance (DOP) upon request.

#### CE Certification

The product is CE marked in accordance with the European standard regarding wooden floors for indoor usage EN 14342.

#### Environment



#### Hørring Parket A/S

Christiansmindevej 12  
DK-8660 Skanderborg  
T: +45 7027 6600  
W: horningfloor.com  
E: sales@horningfloor.dk

**To find further information and inspiration, please visit our website.**

FSC® and/or PEFC available upon request.  
Eurofins Indoor Air Comfort Gold certified.