



Whalebone

Engineered - Data Sheet

HØRNING Whalebone Engineered is available with 4/6 mm wear layer.

Available in a selection of prefinished colours in oil or lacquer, or can be supplied unfinished.

Highlighted Features:

- An exclusive large scale format for spacious interiors
- An exceptionally durable solid wooden floor, crafted to last for generations
- Documented sustainability credentials towards certifications such as BREEAM, DGNB, and LEED through EPDs and Eurofins

If you have any questions or need advice, please don't hesitate to contact us.

13-01-2026

Hørning Parket A/S

Christiansmindevej 12
DK-8660 Skanderborg

T: +45 7027 6600
W: horningfloor.com
E: sales@horningfloor.dk



[epddanmark](http://epddanmark.com)

Whalebone

Engineered - Data Sheet

HØRNING Whalebone Engineered is available in a section of prefinished colours in oil or lacquer, or can be supplied unfinished.

Dimensions & Construction

Type of Wood:	Oak	
Thickness:	16/20 mm	16/20 mm
Width:	100 mm	120 mm
Length:	500 mm	580 mm
Wear Layer:	4/6 mm	4/6 mm

Other dimensions and types of wood are available on request.

Moisture Content: 8% +/- 2%

Description of Gradings

Grades vary from wood species and dimension. Wood is a natural material, thus there will always be variations compared to descriptions and photos. Samples will only show dimension and construction and not the grade. It is certain that variations will exist between small samples and the actual deliveries.

Exquisit:

General uniform colour and wood structure. Variations, due to growth conditions, will exist. In principle, small healthy knots and sapwood may be found. Whirls, small scratches, cross grains, and brown heart may be found to a small extent.

Living:

A more characteristic look with natural colours and wood structure. In principle free of open knots, cracks, pith, etc. Whirls, healthy knots, small scratches, cross grains, and silicon stains may be found. Sapwood or brownheart will be found depending of the wood species.

Country:

A very characteristic look with natural colour variations and structures. Knots, sapwood, and brownheart is found. Very small open knots and scratches may be found.

Profile

Tongue/groove on all four sides. Untreated delivered with sharp edges and oiled with microbevel 4 sides.

Tolerances

Our 100 years of production experience allows us in several product types to offer even lower tolerances.

Thickness:	± 0.2 mm
Width:	+/- 0.2 mm
Length:	+/- 0.1 %
Perpendicular:	+/- 0.2 mm

Surface

Comes untreated, oiled, or lacquered. Other surfaces are available on request.

Installation Method

Fully Gluing	x
Screwing and Nailing	x
Floating	

Underfloor Heating

Underfloor heating may be use – please see our installation guide.

Indoor Climate

It is important that the surface temperature never exceeds 27 degrees!

The relative humidity in the air (R.H.) must always be between 35-65% before, during, and after installation.

Always study the installation guide from Høring prior to installation.

Fire Resistance Class

Dfl-s1 (Untreated)
Cfl-s1 (Prefinished)
Declaration of Performance (DOP) upon request.

CE Certification

The product is CE marked in accordance with the European standard regarding wooden floors for indoor usage EN 14342.

Høring Parket A/S

Christiansmindevej 12
DK-8660 Skanderborg
T: +45 7027 6600
W: horningfloor.com
E: sales@horningfloor.dk

Environment



FSC® and/or PEFC available upon request. Eurofins Indoor Air Comfort Gold certified. EPD available upon request for selected products.

To find further information and inspiration, please visit our website.