



Whalebone

Solid - Data Sheet

HØRNING Solid Whalebone in significant dimensions and patterns - when you require something extra of your room.

Comes in oak and is available in a selection of treatments, including untreated, clear oil, coloured oil, or lacquer.

Highlighted Features:

- A bold and exclusive design, perfectly suited for spacious interiors
- An exceptionally durable solid wooden floor, crafted to last for generations
- Documented sustainability credentials towards certifications such as BREEAM, DGNB, and LEED through EPDs and Eurofins

If you have any questions or need advice, please don't hesitate to contact us.

02-02-2026

Hørning Parket A/S
Christiansmindevej 12
DK-8660 Skanderborg
T: +45 7027 6600
W: horningfloor.com
E: sales@horningfloor.dk



[epddanmark](http://epddanmark.com)

Whalebone

Solid - Data Sheet

HØRNING Solid Whalebone is available in a section of prefinished colours in oil or lacquer, or can be supplied unfinished.

Dimensions & Construction

| | | |
|--|-----------------|-----------------|
| Type of Wood: | Oak | |
| Thickness: | 16 mm | 20 mm |
| Width: | 100/120/150 mm | 100/120/150 mm |
| Length: | 600/800/1000 mm | 600/800/1000 mm |
| Other dimensions and types of wood are available on request. | | |
| Moisture Content: | 8% +/- 2% | |

Description of Gradings

Grades vary from wood species and dimension. Wood is a natural material, thus there will always be variations compared to descriptions and photos. Samples will only show dimension and construction and not the grade. It is certain that variations will exist between small samples and the actual deliveries.

Exquisit:

General uniform colour and wood structure. Variations, due to growth conditions, will exist. In principle free of knots and sapwood. Whirls, small scratches, cross grains, and brown heart may be found to a small extent.

Living:

A more characteristic look with natural colours and wood structure. In principle free of open knots, cracks, pith, etc. Whirls, healthy knots, small scratches, cross grains, and silicon stains may be found. Sapwood or brownheart will be found depending of the wood species.

Country:

A very characteristic look with natural colour variations and structures. Knots, sapwood, and brownheart is found. Very small open knots and scratches may be found.

Profile

Tongue/groove on all four sides. Delivered untreated with sharp edges and oiled with microbevel 4 sides.

Tolerances

Our 100 years of production experience allows us in several product types to offer even lower tolerances.

Thickness:

| | |
|-------------|------------|
| Unfinished | +/- 0.2 mm |
| Prefinished | +/- 0.3 mm |

Width: +/- 0.2 mm

Length: +/- 0.2 mm

Perpendicular: ≤ 0.2%

Surface

Comes untreated. Other surfaces are available on request.

Installation Method

| | |
|----------------------|---|
| Fully Gluing | x |
| Screwing and Nailing | x |
| Floating | |

Underfloor Heating

Underfloor heating may be used – please see our installation guide.

Indoor Climate

It is important that the surface temperature never exceeds 27 degrees!

The relative humidity in the air (R.H.) must always be between 35-65% before, during, and after installation.

Always study the installation guide from Hørning prior to installation.

Fire Resistance Class

Dfl-s1 (Untreated)
Cfl-s1 (Prefinished)
Declaration of Performance (DOP) upon request.

CE Certification

The product is CE marked in accordance with the European standard regarding wooden floors for indoor usage EN 14342.

Hørning Parket A/S

Christiansmindevej 12
DK-8660 Skanderborg
T: +45 7027 6600
W: horningfloor.com
E: sales@horningfloor.dk

To find further information and inspiration, please visit our website.

Environment



FSC® and/or PEFC available upon request. Eurofins Indoor Air Comfort Gold certified. EPD available upon request for selected products.